








AIRFLOW AND FIELD WIRING DIAGRAM

STAND-ALONE FUME HOOD SASH POSITION CONTROL WITH ZONE PRESENCE SENSOR

-  1/4" PNEUMATIC TUBING FURNISHED, INSTALLED AND TERMINATED BY ATC
-  2 CONDUCTOR CABLE FURNISHED, INSTALLED AND TERMINATED BY ATC
-  TWISTED SHIELDED PAIR FURNISHED, INSTALLED, AND TERMINATED BY ATC
-  3 CONDUCTOR SHIELDED CABLE FURNISHED, INSTALLED, AND TERMINATED BY ATC
-  4 CONDUCTOR SHIELDED CABLE FURNISHED, INSTALLED AND TERMINATED BY ATC
-  6 CONDUCTOR SHIELDED CABLE FURNISHED, INSTALLED, AND TERMINATED BY ATC
-  10 CONDUCTOR SHIELDED CABLE FURNISHED, INSTALLED AND TERMINATED BY ATC

ENVIROTRAK CONTROL PANELS REQUIRE 120OR 24 VAC BY OTHERS.

SUBMITTAL COPY

No.	Revision	Date

Architect:	Engineer:	Contractor:	Drawn by:	Chk by:	CAD file:	Date:
		LCS			WebLab11	01/20/20

LABORATORY
STAND-ALONE FUME HOOD SASH POSITION CONTROL WITH ZONE PRESENCE SENSOR

JOB NUMBER	SHEET NO.	OF